



KUBOTA DIESEL ZERO-TURN MOWER



ZD326/ZD331

Kubota's ZD-300 series zero-turn mowers deliver the performance and high quality demanded by commercial operators.

*This information is sourced from overseas and may not necessarily apply locally. It is essential that you confirm specifications and other information with your local Kubota dealer.

Cutting grass is the commercial o And Kubota's ZD-300 series delivers durability, and performance prof





perator's livelihood the power, essionals want.



Day in and day out, you need a professional turf mower that handles non-stop use—a mower that's manoeuvrable, cost effective, and loaded with the features to make your job easier. That's why Kubota developed the ZD-300 series zero-turn commercial mowers—to deliver the results your business demands. The ZD-300 series offers a state-of-the-art Kubota diesel engine, a high-capacity HST transmission, a deep mower deck, and an ultra-comfortable operating area. In short, the ZD-300 series delivers.

KUBOTA DIESEL ZERO-TURN MOWER

The ZD-300 series offers a variety o


ZD326

• 26 Horsepower Kubota diesel engine
• 165 mm-deep, 60"-wide mower deck


TORQUE ECONOMY EASY MAINTENANCE

KUBOTA DIESEL ENGINE

Kubota diesel engines are known for their durability, high performance, energy efficiency and reliability. Kubota diesels offer many advantages over petrol engines: as much as 30%^{*} more fuel efficiency, higher torque, fewer emissions and quieter operation, among others. Kubota engines can aggressively take on heavy mowing jobs for extended periods. And, whether it's our 26 or 31-horsepower engine, it will exceed the high expectations of the commercial landscaper.



*Results vary by the engine settings, grass conditions, terrain, etc.



f models to meet a variety of needs.

ZD331

31 Horsepower Kubota diesel engine
165 mm-deep, 72"/60"-wide mower deck



DUAL-ELEMENT AIR CLEANER

Kubota ZD-300 series mowers come equipped with a dual-element air cleaner which features a vacuum sensor to tell you when to service the air cleaner.



LARGE FUEL TANK

Kubota has increased the fuel capacity for the ZD-300 series to 45 litres by including two fuel tanks. This allows the operator to work longer and more efficiently without stopping to refuel. This feature is especially handy for those big jobs.



LARGE RADIATOR

The radiator on the ZD-300 mower is built to improve cooling performance and prevent the engine from overheating.

Kubota's new high-capacity transmission system makes the ZD-300 exceptionally durable.

The ZD-300 series is extremely reliable, thanks in no small part to the new Kubota integral-type HST transmission system. It's designed with strong components and the high capacity an HST system needs to assure outstanding commercial mowing performance and productivity.

HST TRANSMISSION

With an increased HST capacity of 120%, and a 30% increase in hydraulic clutch transfer capacity, Kubota's HST system optimises performance to achieve maximum results. It's regulated by a new external, gear hydraulic charge pump for smoother control, quieter operation, and quicker overall response. Kubota's HST transmission system will last longer, run more reliably, and perform to a higher standard.

DURABILITY






PTO CLUTCH

Thanks to a wearresistant, wet-type, multidisk, hydraulic PTO clutch, the machine will work longer, but not harder. That's because it smoothly transfers power with maximum efficiency. For safety, the PTO clutch is also equipped with an internal brake, which stops the mower blades quickly after disengagement.

DURABILITY

Kubota's HST transmission system is comprised of high-strength components for exceptional durability. With a copper metal cylinder block, a stronger rear tyre axle, and a sturdy, lightweight casting axle cover, the HST system is designed and built to last a long time.





FI (S Th we im st er

SEMI-PNEUMATIC (FLAT-FREE) FRONT CASTER TYRES (Standard with ZD331)

The ZD-300's flat-free caster tyres were specifically designed to absorb impacts with the rigidity of their structural thickness. This feature enables mowing operations to continue without the worry of downtime from flat tyres.



SHAFT DRIVE

The direct transfer of power from our shaft drive is smooth. Plus, our shaft drive's lowmaintenance operation makes it the most dependable choice.

The ZD-300 is built for comfort, so there's less fatigue and more productivity.

The ZD-300 series brings comfort to the workplace. Kubota's development team has created a mower loaded with creature comforts. From the deluxe, high-back seat to the ergonomically engineered control panel, the comfortable design and practical convenience of the ZD-300 make it easier to boost productivity.

OPERATOR PLATFORM

The ZD-300's comfortable operator platform boasts a wide array of features designed to make work easier. Wider control levers and a full-flat operator platform allow greater legroom; the angled panel helps to prevent glare for easier indicator and control viewing. In addition, the ZD-300 offers an ergonomic, 4-control adjustable seat to prevent fatigue and a conveniently placed cup holder so you can quench your thirst on the job.

COMFORT

ADJUSTABLE LEVERS The angle of the speed control levers can be shifted by 19° forward and backward, and their height **CUP HOLDER** can be increased or decreased by an inch, giving you more legroom, 99 mm widt better reach and increased comfort. Even the grip size is larger to reduce fatigue. FRONT COVER With a durable new steel cover to protect the front of the mower, as well as the maintenance lift, the ZD-300 will be less susceptible to damage during truck loading and unloading



PANEL

With a new, ergonomically angled control panel, you'll have an improved view of and easier access to the controls and indicators, including speed controls, fuel and oil gauges, the all-new 1/4" cutting height adjustment dial, the locking PTO lever and more.



PARKING BRAKE (Hands-free)

With the ZD-300, you don't need separate levers or special switches to set the parking brake; you only need to depress the parking pedal and set the parking lock. Both are conveniently placed directly in front of you on the angled footboard for easy access.

HIGH-BACK DELUXE SUSPENSION SEAT

Outstanding comfort is what you'll feel with Kubota's standard deluxe link-type suspension seat with adjustable armrests. The extra-wide seat features weight adjustment, adjustable armrests, and much more to give the operator a custom fit.

LUMBAR SUPPORT

A day of hard work won't be hard on your back. Thanks to the 3-position lumbar support offered by the ZD-300, your back will get all the support it needs.



SUSPENSION SEAT ADJUSTMENT LEVER

There's no need to get up to make changes to your seat's suspension strength—you simply reach down in front of you and pull this convenient lever to make adjustments while you're working.

RECLINING DIAL

Lean back and get to work in the ZD-300's reclining seat. Just reach to the side and turn the handy reclining dial to adjust your seat to the perfect position.





Take care of the ZD-300 and the ZD-300 will take care of business.

Kubota has made maintenance of the ZD-300 unbelievably simple. Thanks to a unique maintenance lift system, a tilt-up seat for quick and thorough access to the HST, and a new maintenance hatch on the full-flat platform for easy access to the PTO shaft, work can be completed on every key component without difficulty.

EASY MAINTENANCE

Maintenance has never been so easy. For interior maintenance, the sturdy seat panel is simply lifted up for clear access and an unobstructed view. By opening the hood, it's easy to perform routine maintenance, like adding oil, in mere seconds. Plus, there's a new maintenance hatch on the full-flat platform, with a built-in storage pocket, for easy access to the upper mower, gearbox case and universal joint parts.

MAINTENANCE









MAINTENANCE LIFT

For routine maintenance underneath the mower, Kubota's unique two-pin, tilt-up, lift feature allows the front of the ZD-300 to be easily raised without having to remove the mid-mount mower. The system includes locks for the front tyres to ensure safety. It's like having a built-in jack right there when you need it.



RADIATOR SCREEN Kubota has now integrated the radiator screen into the bonnet for better sealing performance and less likelihood of grass clippings finding their way inside the screen.



AIR CLEANER INDICATOR The ZD-300 features an air cleaner indicator that indicates when it's time to change or clean the filter, and help maintain maximum airflow capacity.



ENGINE COOLANT ALERT The ZD-300 emits a warning alert to indicate when engine coolant temperatures run too high. It's another practical feature that helps keep this commercial mower running smoothly.



TIE DOWN This strong and durable tie down is ideal for securing and loading the ZD-300 onto a flatbed truck, making transportation a breeze.

Kubota's new mower deck is deeper for exceptional cutting performance.

You're a professional, and your equipment should meet your high, exacting standards. This is why the ZD-300 zero-turn mowers are equipped with the kind of powerful, rugged, commercial-grade mower deck you want and your business demands. It's everything you need to reach a higher level of performance.

PRO COMMERCIAL MOWER DECK

To ensure superior cutting performance, even at faster speeds, our newly developed, deeper mower deck utilises a flat design and our unique new baffling system, which forces grass through all three cutting blades. And, to meet the needs of varying job sizes, the ZD-300 mower deck is available in two sizes: 72" and 60".

MOWER DECK

DEEP MOWER DECK

Kubota's extra-deep, 165 mm, fabricated mower deck design allows for faster cutting—even in tall, thick, and wet grass. The discharge chute is 27% wider, to dispense clippings more evenly across the ground.



PREVIOUS ZD PRO MOWER DECK



ZD-300 SERIES MOWER DECK



SWIVEL ANTI-SCALP ROLLERS To prevent unsightly turf damage, we've equipped the 72" and 60" mower decks with independently functioning anti-scalp rollers that rotate a full 360 degrees.





STANDARD BLADE

Combined with a deep mower deck for expanded clipping capacity, the ZD-300's standard blade provides a higher quality, beautiful-looking cut.



SPINDLE BEARINGS AND PULLEYS

Kubota has improved the durability of the mower pulley holder bearings to provide maximum strength and support.

Kubota's Side-Discharge System brings professional results with less effort.



ANTI-OVERFLOW SYSTEM

Kubota has enhanced the edges of the mower deck to reduce grass spillage and help keep lawns tidy, particularly in dry conditions.

NEW BAFFLE DESIGN

The ZD-300's new baffle design improves air flow to discharge grass clippings, optimising cutting performance.

FLEXIBLE DISCHARGE CHUTE

The mower deck's discharge chute is crafted from a flexible-but-sturdy material, which helps considerably reduce damage to brush and landscaping.



Now you can elevate the mower deck and literally roll right over obstacles, thanks to the ZD-300 mower hydraulic deck lift.

LARGE-DIAMETER REAR TYRES The ZD-300 features large-diameter, sturdy

The ZD-300 features large-diameter, sturdy rear tyres for improved stability, durability and handling. The ZD331 with 72" mower deck and the ZD326 with 60" mower deck come standard with big 26x12.0-12 tyres.





1/4" INCREMENT CUTTING HEIGHT ADJUSTMENT

Cutting height can be easily changed, from 1" to 5" in 1/4" increments, with the 1/4" adjustment dial. Located conveniently on the control panel, the adjustment dial is easily accessed to increase or decrease cutting height.



MOWER LIFT LINK

The ZD-300 mowers feature stronger lift link components, including an enhanced lift shaft, a thicker lift arm, and a wider shaft diameter.

OPTIONAL ATTACHMENTS

Kubota produces a superior mulch.

NEW ZD-300 MULCHING SYSTEM

The deep mower deck of the Kubota ZD-300 is perfect for mulching, even on thick grass. A Kubota original flow plate has been added to the closed-system design to optimise airflow and facilitate repeated cutting. The mulching blades are designed to provide an extra-fine cut to leave a beautiful finish.

KUBOTA

MULCHING BLADES Forged from high-quality steel, our ZD-300 mulching blades are incredibly sharp and hold their



razor-like edges longer.

"CATCH ALL" GRASS CATCHER (GCK60-331Z*)

The blower forces clippings into a large, 430-litre hopper, allowing the operator to mow longer over a larger area without stopping as often to empty clippings. For the quick removal of grass clippings, the hopper lid is simply unlocked and the bag slides out.

*Requires blower kit.

Specifications

opcomo					
Model			ZD326	ZD331	
			ZD326P-60	ZD331LP-72	
Engine	Model		Kubota D1005 Kubota D1305		
	Туре		Diesel, liquid-cooled (3 cyl.)		
	Max. horsepower (Gross)		26HP@3200rpm	31HP@3000rpm	
	Total displacement		1001cc	1261cc	
	Starting system		Key switch - super glow		
Dimensions	Overall length		2220 mm	2335 mm	
	Overall width Overall height	(w/ mower)	1910 mm	2223 mm	
		(w/o mower)	1460 mm		
		(w/ ROPS upright)	1915 mm		
		(w/ ROPS folded)	1555 mm		
Wheel base			1410 mm	1525 mm	
Tread	Front		975 mm	1070 mm	
	Rear		1150 mm		
Tyre size	Front		15×6.0-6	$15 \times 6.0-6$ Non Flat	
	Rear		26	× 12.0-12	
Weight (w/ mower) (without fuel)		fuel)	756 kg	803 kg	
Transmission system			2-HST w/ Gear		
Speed control			2-hand lever		
Travel speed Forward			0-17.0 km/h		
range	Reverse		0-8.5 km/h		
Brake type			Wet multi disks, foot operated		
РТО	Туре		Shaft drive		
	Clutch type		Wet multi disk		
	PTO brake		Wet single disk		
Mower deck	Model		RCK60P-331Z RCK72P-331Z		
	Mower lift system		Hydraulic		
	Mower deck type		Fabricated deck		
	Deck depth		165 mm		
	Deck steel thickness		4.6 mm, 4.2 mm		
	Anti-scalp roller		Swivel		
	Cutting width of mower		60 in.	72 in.	
	Number of blades			B blades	
	Cutting height		1 in. ~ 5 in. / 1/4 in. increments		
	Mounting system of mower		Parallel linkage		
	Blade tip speed (max.)		18200 FPM	18100 FPM	
Sect adjustm		eu (max.)			
Seat adjustment Step deck			One touch system (weight, armrests, reclining, and lumbar support) Full flat		
Engine stop system			Key stop		
Fuel tank capacity			45 ltrs.		
Battery			43 ms. 12 Volts, 51R, 450CAA@0° F, 70 min. RC.		
Alternator capacity					
Water temperature indicator			14 Volts 14 Amps		
•			Standard		
Hour meter					
Fuel gauge			Electric		

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, KUBOTA strongly recommends the use of a Roll-Over Protective Structure (ROPS) and seat belt in almost all applications.

Kubota

KUBOTA Tractor Australia Pty Ltd

100 Keilor Park Drive, Tullamarine Vic., 3043 Freecall: 1800 334 653 Email: sales@kubota.com.au Web Site: http://www.kubota.com.au

©2007 Kubota Corporation